



NEW !

Art.-No.	Description
	<p>EBS/ABS-socket 7-pin according to ISO 7638</p> <ul style="list-style-type: none"> · Injected seal in housing · Controlled GGVS and ADR · For cable section 8-12,5 mm · 5 x 1,5 mm² + 2 x 4 mm² · Massive contact with crimp connection · Contact insert with seal · OEM-Version · Available with hand crimping tools
785 420 500	<p>Version: cable exit with screw cap nut</p> <p>Pin contacts and seals (7 pieces) incl.</p>
785 420 600	<p>Version: conduit exit</p> <p>Incl. pin contacts (7 pcs) and seals, conduit exit axial NW13</p>
785 420 700	<p>Incl. pin contacts (7 pcs) and seals, conduit exit 90° NW13</p>
785 420 800	<p>Incl. pin contacts (7 pcs) and seals, conduit exit axial NW17</p>
785 420 900	<p>Incl. pin contacts (7 pcs) and seals, conduit exit 90° NW17</p>
785 220 300	<p>Park socket 24 V</p>
	<p>Additional parts</p>
785 125 000	Socket housing with cover
785 420 080	Contact insert EBS 7-pin with seal
785 120 080	Contact insert ABS 5-pin with seal
785 120 050	Bayonet ring
785 120 030	Conduit exit axial NW13
785 120 040	Conduit exit 90° NW13
785 120 060	Conduit exit axial NW17
785 120 070	Conduit exit 90° NW17
	<p>Accessories</p>
785 130 911	Massive pin contact with crimp connection 1 - 2,5 mm² Individual pin contact
785 130 910	Reel of 1.200 pcs
785 110 940	Single wire seal 1-2,5 mm ² (2.500 pcs)
785 130 921	Massive pin contact with crimp connection 4 mm² Individual pin contact
785 130 920	Reel of 1.200 pcs
785 110 950	Seal 4 mm ² (2.500 pcs)

